# **SAFETY DATA SHEET**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

**BLACK CURRANT FLAVOR N&A TYPE** 

of the mixture

Registration number

Synonyms None.

Product code SLP107

Issue date 22-August-2017

Version number 01

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses**Use in accordance with supplier's recommendations.

Uses advised against No other uses are advised.

#### 1.3. Details of the supplier of the safety data sheet

Supplier

Company name Capella Flavors, Inc.
Address 6155 Corte Del Cedro
Carlsbad. CA 92011

**United States** 

**Division** 

Telephone Office 760 650-0200

Fax n/a

e-mail customerservice@capellaflavors.com

Contact person Not available.

1.4. Emergency telephone CHEMTREC

number

INTERNATIONAL 703-741-5500

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

800-424-9300

## Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Not classified for health hazards. However, occupational exposure to the mixture or substance(s)

may cause adverse health effects.

2.2. Label elements

## Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word None.

Hazard statements The mixture does not meet the criteria for classification.

**Precautionary statements** 

**Prevention** Observe good industrial hygiene practices.

**Response** Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Supplemental label information EUH208 - Contains TRADE SECRET, TRADE SECRET. May produce an allergic reaction.

**2.3. Other hazards**Not a PBT or vPvB substance or mixture.

## **SECTION 3: Composition/information on ingredients**

3.2. Mixtures

SLP107 Version #: 01 | Issue date: 22-August-2017

#### **General information**

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
ETHYL ALCOHOL 190 CANE IP NON GMO	PROOF	1-<3	64-17-5 200-578-6	-	603-002-00-5	
Classification:	Flam. Liq	. 2;H225, Eye	Irrit. 2;H319			
TRADE SECRET		<1	Proprietary -	-	-	
Classification:	Skin Sens	s. 1B;H317				
TRADE SECRET		< 0,3	Proprietary	-	-	
Classification:	Acute Tox	k. 4;H312, Ski	- n Irrit. 2;H315, Skin	Sens. 1;H317, Eye Irrit. 2;H31	9	

Other components below reportable levels 90 - 100

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

#### **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms

and effects, both acute and

delayed

Exposure may cause temporary irritation, redness, or discomfort.

4.3. Indication of any Treat symptomatically.

immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising

from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Special protective

equipment for firefighters

Special fire fighting

Move containers from fire area if you can do so without risk.

procedures Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

Avoid discharge into drains, water courses or onto the ground. 6.2. Environmental precautions

Material name: BLACK CURRANT FLAVOR N&A TYPE **SLP107** Version #: 01 Issue date: 22-August-2017

#### 6.3. Methods and material for containment and cleaning up

Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

# 6.4. Reference to other

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

sections

## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10

Value

of the SDS).

7.3. Specific end use(s)

Not available.

Type

## **SECTION 8: Exposure controls/personal protection**

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

#### 8.1. Control parameters

Components

## Occupational exposure limits

Components	Type	
ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	Ceiling	3800 mg/m3
GIVIO (CAS 04-17-3)		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Belgium. Exposure Limit Values.		
Components	Туре	Value
ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	TWA	1907 mg/m3
civic (cric or ir o)		1000 ppm
Bulgaria. OELs. Regulation No 13 on	protection of workers against r	sks of exposure to chemical agents at work
Components	Туре	Value
ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	TWA	1000 mg/m3
Croatia. Dangerous Substance Expo	sure Limit Values in the Workpla	ice (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
Components	Туре	Value
ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	MAC	1900 mg/m3
GIVIO (CAS 04-17-5)		1000 ppm
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	MAC	10 mg/m3
110111 1111 (6/16/67/66/67)		150 ppm
Creek Benuklie OELe Covernment	Decree 361	
CZECII REDUDIIC. OELS. GOVERNMENT I		
	Туре	Value
Czech Republic. OELs. Government Components ETHYL ALCOHOL 190 PROOF CANE IP NON		Value 3000 mg/m3
Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Туре	3000 mg/m3
Components  ETHYL ALCOHOL 190  PROOF CANE IP NON  GMO (CAS 64-17-5)	<b>Type</b> Ceiling	
Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Denmark. Exposure Limit Values	Type Ceiling TWA	3000 mg/m3
Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Denmark. Exposure Limit Values Components	Type Ceiling TWA Type	3000 mg/m3 1000 mg/m3 <b>Value</b>
Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Denmark. Exposure Limit Values	Type Ceiling TWA	3000 mg/m3 1000 mg/m3

Material name: BLACK CURRANT FLAVOR N&A TYPE

SLP107 Version #: 01 Issue date: 22-August-2017

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September	•
2001)	

2001) Components	Туре	Value
PROOF CANE IP NON	STEL	1900 mg/m3
GMO (CAS 64-17-5)		1000 ppm
	TWA	1000 mg/m3
		500 ppm
inland. Workplace Exposure Limits		
Components	Туре	Value
THYL ALCOHOL 190	STEL	2500 mg/m3
PROOF CANE IP NON		<b>G</b>
GMO (CAS 64-17-5)		1300 ppm
	TWA	1900 mg/m3
		1000 ppm
rance. Threshold Limit Values (VLEP) f	or Occupational Exposure to Che	• •
omponents	Туре	Value
-		
THYL ALCOHOL 190 ROOF CANE IP NON SMO (CAS 64-17-5)	VLE	9500 mg/m3
( /		5000 ppm
	VME	1900 mg/m3
		1000 ppm
ermany. DFG MAK List (advisory OELs n the Work Area (DFG)	s). Commission for the Investigati	on of Health Hazards of Chemical Compounds
components	Туре	Value
THYL ALCOHOL 190	TWA	960 mg/m3
PROOF CANE IP NON		
PROOF CANE IP NON GMO (CAS 64-17-5)		500 mars
		500 ppm
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the	Ambient Air at the Workplace Type	500 ppm  Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components		
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Туре	Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Туре	Value 960 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	Type AGW	Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an	Type  AGW mended)	Value 960 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an components	Type  AGW  mended) Type	Value 960 mg/m3 500 ppm Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190	Type  AGW mended)	<b>Value</b> 960 mg/m3 500 ppm
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Type  AGW  mended) Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Type  AGW  mended) Type	Value 960 mg/m3 500 ppm Value
GMO (CAS 64-17-5) Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic	Type  AGW  mended) Type  TWA	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm
Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  GROOF CANE IP NON GMO (CAS 64-17-5)	Type  AGW  mended) Type  TWA	Value  960 mg/m3  500 ppm  Value  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as alcomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic components	Type  AGW  mended) Type  TWA  cal Safety of Workplaces	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as alcomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm
GMO (CAS 64-17-5) Germany. TRGS 900, Limit Values in the components GTHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Greece. OELs (Decree No. 90/1999, as all components GTHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Jungary. OELs. Joint Decree on Chemic components GTHYL ALCOHOL 190 PROOF CANE IP NON GROOF CANE IP NON	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3
GMO (CAS 64-17-5) Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  GROOF CANE IP NON GMO (CAS 64-17-5)	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  CELSTAN COMPONENT C	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  coccupational exposure limits	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as alcomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  CELANDER OF CANE IP NON GMO (CAS 64-17-5)  CELANDER OF CANE IP NON GMO (CAS 64-17-5)  CELANDER OF CANE IP NON GMO (CAS 64-17-5)	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  ccupational exposure limits Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  GTHYL ALCOHOL 190 GROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as all components  GTHYL ALCOHOL 190 GROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic components  GTHYL ALCOHOL 190 GROOF CANE IP NON GMO (CAS 64-17-5)  Geland. OELs. Regulation 154/1999 on components  GTHYL ALCOHOL 190  Geland. OELs. Regulation 154/1999 on components	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  coccupational exposure limits	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as alcomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on ocomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON COMPONENTS	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  ccupational exposure limits Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as alcomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on occomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON CENTRAL OF CANE IP NON	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  ccupational exposure limits Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3
GMO (CAS 64-17-5) Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Hungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on occomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  CELANDER OF CANE IP NON GMO (CAS 64-17-5)	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  ccupational exposure limits Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3  Value  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Jungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OCCUpational Exposure Limits	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  ccupational exposure limits Type	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3  Value  1900 mg/m3
GMO (CAS 64-17-5)  Germany. TRGS 900, Limit Values in the Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Greece. OELs (Decree No. 90/1999, as an Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Hungary. OELs. Joint Decree on Chemic Components  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on occomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. OELs. Regulation 154/1999 on occomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)  Celand. Occupational Exposure Limits Components	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  occupational exposure limits Type  TWA  Type	Value         960 mg/m3         500 ppm         Value         1900 mg/m3         Value         7600 mg/m3         Value         1900 mg/m3         Value         1900 ppm         Value         Form
	Type  AGW  mended) Type  TWA  cal Safety of Workplaces Type  STEL  TWA  cccupational exposure limits Type  TWA	Value  960 mg/m3  500 ppm  Value  1900 mg/m3  1000 ppm  Value  7600 mg/m3  1900 mg/m3  Value  1900 mg/m3  1000 ppm

Material name: BLACK CURRANT FLAVOR N&A TYPE SLP107 Version #: 01 Issue date: 22-August-2017

reland. Occupational Exposure Limits Components	Туре	Value Form	
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TWA	470 mg/m3 Total vapo particula	
		10 mg/m3 Particula	
		150 ppm Total vap particula	
taly. Occupational Exposure Limits		particule	ates.
Components	Туре	Value	
THYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	STEL	1000 ppm	
.atvia. OELs. Occupational exposure lim	nit values of chemical substa Type	ances in work environment Value	
ETHYL ALCOHOL 190	TWA	1000 mg/m3	
PROOF CANE IP NON			
GMO (CAS 64-17-5)	T) A / A	7 / 2	
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TWA	7 mg/m3	
ithuania. OELs. Limit Values for Chemi		-	
Components	Туре	Value	
ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	STEL	1900 mg/m3	
-/		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
PROPYLENE GLYCOL	TWA	7 mg/m3	
IOM NFI (CAS 57-55-6)		<b>3</b>	
letherlands. OELs (binding)	_		
components	Туре	Value	
THYL ALCOHOL 190 ROOF CANE IP NON SMO (CAS 64-17-5)	STEL	1900 mg/m3	
	TWA	260 mg/m3	
Norway. Administrative Norms for Conta	<del>-</del>	Malica	
Components	Туре	Value	
ETHYL ALCOHOL 190 PROOF CANE IP NON	TLV	950 mg/m3	
GMO (CAS 64-17-5)		500	
	<b>-</b> 1.5.4	500 ppm	
	TLV	79 mg/m3	
PROPYLENE GLYCOL NOM NEL (CAS 57-55-6)			
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)		25 ppm	
NOM NFI (CAS 57-55-6)  Poland. MACs. Minister of Labour and So	ocial Policy Regarding Maxi	25 ppm mum Allowable Concentrations and Intensitie	es in
NOM NFI (CAS 57-55-6)	ocial Policy Regarding Maxi		es in
NOM NFI (CAS 57-55-6)  Poland. MACs. Minister of Labour and So  Vorking Environment  Components	Туре	mum Allowable Concentrations and Intensitie	es in
NOM NFI (CAS 57-55-6)  Poland. MACs. Minister of Labour and Soverking Environment		mum Allowable Concentrations and Intensitie	es in
Poland. MACs. Minister of Labour and So Vorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON	<b>Type</b> TWA	Walue 1900 mg/m3	es in
Poland. MACs. Minister of Labour and So Vorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)	<b>Type</b> TWA	Walue 1900 mg/m3	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents ETHYL ALCOHOL 190	Type  TWA  xposure to chemical agents	Value 1900 mg/m3  (NP 1796)	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents	Type  TWA  xposure to chemical agents Type	Value 1900 mg/m3  (NP 1796)  Value	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) ROMAN (CAS 64-17-5) Romania. OELs. Protection of workers fr	Type TWA  xposure to chemical agents Type TWA  rom exposure to chemical agents	Value  1900 mg/m3  (NP 1796)  Value  1000 ppm	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON EMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents ETHYL ALCOHOL 190 PROOF CANE IP NON EMO (CAS 64-17-5)	Type TWA  xposure to chemical agents Type TWA  rom exposure to chemical ag Type	Value  1900 mg/m3  (NP 1796)  Value  1000 ppm	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Romania. OELs. Protection of workers frecomponents ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Romania. OELs. Protection of workers frecomponents	Type TWA  xposure to chemical agents Type TWA  rom exposure to chemical agents	Value  1900 mg/m3  (NP 1796)  Value  1000 ppm	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components  ETHYL ALCOHOL 190 PROOF CANE IP NON Components  Portugal. VLEs. Norm on occupational excomponents  ETHYL ALCOHOL 190 PROOF CANE IP NON COMPONENT	Type TWA  xposure to chemical agents Type TWA  rom exposure to chemical ag Type	Value  1900 mg/m3  (NP 1796)  Value  1000 ppm  gents at the workplace Value	es in
Poland. MACs. Minister of Labour and Solvorking Environment Components ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Portugal. VLEs. Norm on occupational excomponents ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5) Romania. OELs. Protection of workers freedomponents	Type TWA  xposure to chemical agents Type TWA  rom exposure to chemical ag Type	Value  1900 mg/m3  (NP 1796)  Value  1000 ppm  gents at the workplace Value	es in

Material name: BLACK CURRANT FLAVOR N&A TYPE SLP107 Version #: 01 Issue date: 22-August-2017

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Personal protection equipment should be chosen according to the CEN standards and in **General information** 

discussion with the supplier of the personal protective equipment.

Wear safety glasses with side shields (or goggles). Eve/face protection

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection

- Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Liquid. Physical state Liquid. **Form** Colour Not available. Odour Not available. **Odour threshold** Not available.

Not available. pН

Initial boiling point and boiling

188,2 °C (370,76 °F) estimated

-59 °C (-74,2 °F) estimated

range

Melting point/freezing point

70,8 °C (159,4 °F) Closed cup Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Not available.

(%)

(%)

Flammability limit - upper

Vapour pressure 0,13 hPa estimated Vapour density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

371,11 °C (700 °F) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. **Viscosity** Not available. **Explosive properties** Not explosive. Not oxidising. **Oxidising properties** 

9.2. Other information

Refractive index 1,3972 - 1,4272 1,01 - 1,04 Specific gravity

## **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. 10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

No hazardous decomposition products are known. 10.6. Hazardous

decomposition products

10.4. Conditions to avoid

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation

may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity No data available.

Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. Serious eye damage/eye

irritation

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. Skin sensitisation Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work

(as amended) Not listed.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure **Aspiration hazard** 

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information May cause allergic respiratory and skin reactions.

**SECTION 12: Ecological information** 

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

ETHYL ALCOHOL 190 PROOF CANE IP NON GMO -0.31

**Bioconcentration factor (BCF)** Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT Not a PBT or vPvB substance or mixture.

and vPvB assessment

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

SDS FU 8 / 10 **Residual waste**Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**Disposal methods/information**Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

**Special precautions**Dispose in accordance with all applicable regulations.

#### **SECTION 14: Transport information**

**ADR** 

14.1. - 14.6.: Not regulated as dangerous goods.

**RID** 

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN** 

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of Marpol

and the IBC Code

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not established.

#### **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I, as amended

Not listed

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

NOL IISLEU

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

## **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

## Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ETHYL ALCOHOL 190 PROOF CANE IP NON GMO (CAS 64-17-5)

Material name: BLACK CURRANT FLAVOR N&A TYPE
SLP107 Version #: 01 Issue date: 22-August-2017

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

> Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. Additional information is given in the Safety Data Sheet.

**National regulations** 15.2. Chemical safety Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

assessment

#### **SECTION 16: Other information**

List of abbreviations Not available. References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements

not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

**Revision information** 

Follow training instructions when handling this material.

**Training information** Disclaimer

Capella Flavors, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Material name: BLACK CURRANT FLAVOR N&A TYPE

**SLP107** Version #: 01 Issue date: 22-August-2017